

EASYPSV® APPLICATION INSTRUCTIONS

- 1. Place EasyPSV with the liner side down and cut your design. (DO NOT reverse / mirror your design.)
- 2. Weed the excess vinyl.
- 3. Remove the application tape's paper liner. Place the tape on top of EasyPSV and burnish with a squeegee.
- 4. Lift the application tape and EasyPSV away from the paper liner to expose the removable adhesive.
- 5. Place the application tape with your design on your desired object.
- 6. Burnish with a squeegee to fully adhere the design.
- 7. Gently peel away the application tape, leaving just your EasyPSV design on the object.

EASYPSV® STARLING™

Specifications: Smooth opaque / high gloss finish · 76 microns · 45° Blade

Outdoor Durability	Up to 5 years depending on climate and UV exposure.
Adhesive	Permanent, Clear Acrylic
Liner	78# Bleached Kraft
Minimum, Application Temperature	10 °C
Shelf Life	2 years when stored at 20-25 °C and 50% relative humidity.
Romeo / Juliet Cut Settings	Speed: 10 / Force: 5

Dishwasher safe up to 80 washes.

Not recommended for use with microwave, or painted drywall.

EASYPSV® GLITTER

Specifications: Smooth gloss finish · 76 microns · 45° Blade

Outdoor Durability	Up to 5 years depending on climate and UV exposure.
Adhesive	Permanent, Acrylic
Liner	78# Kraft
Minimum, Application Temperature	10 °C
Shelf Life	2 years when stored at 20-25 °C and 50% relative humidity.
Romeo / Juliet Cut Settings	Speed: 10 / Force: 5

Not recommended for use with dishwasher, microwave, or painted drywall.

Recommended Accessories: Cutting Machine, Siser® Weeder®, EasyPSV® Mask, Siser® Squeegee







