

# P.S. LUMEN - EASYWEED GLOW IN THE DARK

## **SPECIFICATIONS**

| Composition            | ्रं<br>Avarage Thickness | Carrier            | & Certifications           |  |  |
|------------------------|--------------------------|--------------------|----------------------------|--|--|
| PU<br>photoluminescent | 100 microns              | Adhesive polyester | REACH n° 1907/2006/EU      |  |  |
|                        |                          |                    | VEGANOK<br>AZIENDA N. 1004 |  |  |

# APPLICATION INSTRUCTIONS

| ⊗<br>Applies on  | SUGGESTED CUTTING SETTINGS |                  |           | TRANSFER SETTINGS |                  |                         |          |
|--|----------------------------|------------------|-----------|-------------------|------------------|-------------------------|----------|
| cotton, polyester, poly/<br>cotton blends<br>(not suited for treated | Blade                      | <u></u> Pressure | >> Speed  | Time              | Temperature      | Pressure                | Peel     |
| `and dye sublimated<br>textiles)                                     | 45°                        | 80 gf            | 30 cm/sec | 15 seconds        | 150°C<br>(302°F) | Medium<br>(2,5/3,5 bar) | hot/cold |

- → Cut the material mirrored
- → Peel off excess material
- → Place the decoration on the garment
- → Apply following the recommended parameters
- ightarrow Remove the carrier hot or cold

#### **PRODUCT HIGHLIGHTS**

→ Long-lasting photoluminescent effect

NOTE: We highly recommend to perform a test before launching a production.

## CARE AND WASHING RECOMMENDATIONS

| Washing                  | Ironing           | Tumble dry               | Ony cleaning | Storage<br>Shelf Life | Storage<br>Temperature   | Storage<br>Conditions             | <b>∮</b><br>Position |
|--------------------------|-------------------|--------------------------|--------------|-----------------------|--------------------------|-----------------------------------|----------------------|
| Up to 40°C<br>inside-out | YES<br>inside-out | YES<br>(synthetic cycle) | NO           | Up to 2 years         | Between 18°C<br>and 26°C | Away from<br>sunlight and<br>dust | Vertical             |

- → Wait 24 hours after the application before the first wash
- → Respect the textile recommendations
- → Do not bleach or use aggressive chemical agents

This document can be subject to variations. Updated versions are available on www.siser.com. For further information, please contact our sales office: info@siser.it



Siser s.r.l. Viale della Tecnica, 18 36100 Vicenza - Italy Tel. +39 0444.287960 Fax +39 0444.287959 info@siser.it www.siser.com r.e.a. vi 171856 reg. imp. vi n° 14971 c.s. € 103.300 i.v. p.iva 01591490246



