

## P.S. STRETCH-EASYWEED<sup>™</sup> STRETCH

# SPECIFICATIONS Specifications Image: Composition Image: Carrier Image: Carrier Image: Carrier Image: Carrier PU 90 microns adhesive polyester REACH n° 1907/2006/EU Image: Carrier Image: Carrier Image: Carrier Image: Carrier PU 90 microns adhesive polyester Image: Carrier

### 

⊘ Applies on	SUGGES		SETTINGS	TRANSFER SETTINGS			
cotton, polyester, poly/ cotton blends,elastan (not suited for treated	<b>▲</b> Blade	<b>≚</b> Pressure	» Speed	© Time	Temperature	<u>←</u> Pressure	● Peel
and dye sublimated textiles)	45°	50 gf	20 cm/sec	20 seconds	160°C (320°F)	Medium ( 2,5/3,5 bar)	hot

- → Cut the material mirrored
- → Peel off excess material
- ightarrow Place the decoration on the garment
- → Apply following the recommended parameters
- $\rightarrow$  Remove the media while hot

#### ADVANTAGES OF THE PRODUCT

- → Reduced thickness
- → Matte Finish
- → High elasticity

☑ NOTE: We highly recommend to perform a test before launching a production

#### CARE AND WASHING RECOMMENDATIONS

₩ Washing	Reference to the second	🖸 Tumble dry	O Dry cleaning	C Storage Shelf Life	ें Storage Temperature	C Storage Conditions	<b>∮</b> Position
Up to 60°C, best inside- out	YES best inside-out	YES (cotton cycle)	NO	Up to 2 years	Between 18°C and 26°C	Away from sunlight and dust	Vertical

 $\rightarrow$  Wait 24 hours after the application before the first wash

- → Respect the textile recommendations
- → Do not bleach or use aggressive chemical agents

This document can be subject to variations. Updated versions are available on www.siser.com. For further information, please contact our sales office: info@siser.it



Siser s.r.l. Viale della Tecnica, 18 36100 Vicenza - Italy Tel. +39 0444.287960 Fax +39 0444.287959 info@siser.it www.siser.com r.e.a. vi 171856 reg. imp. vi n° 14971 c.s. € 103.300 i.v. p.iva 01591490246

